



# MASTERLine ES

## MASTERLine ES 45W GU5.3 12V 36D 1CT/4X5F

Low-voltage halogen burner with very high energy efficiency and long lifetime thanks to IRR coating in glass reflector. Ideal solution for small decorative luminaires, putting your objects in the spotlight. Dichroic coating prevents heat transmission onto the object.

### Product data


General Information	
Cap base	GU5.3 [ GU5.3]
Philips code	18144
Operating position	UNIVERSAL [ Any or Universal (U)]
ANSI code halogen	na [ not applicable]
Nominal lifetime (nom.)	5000 h
Switching cycle	20000X
Light Technical	
Beam Angle (Nom)	36 °
Luminous flux (rated) (nom.)	830 lm
Luminous intensity (max.)	2850 cd
Rated beam angle	36 °
Correlated colour temperature (nom.)	3000 K
Color rendering index (nom.)	100
LLMF at end of nominal lifetime (min.)	80 %
Luminous Flux in 90° Cone (Rated)	830 lm
Operating and Electrical	
Power (Rated) (Nom)	45.0 W
Lamp current (nom.)	3.75 A
Wattage equivalent	68 W
Starting time (nom.)	0.0 s

Warm-up time to 60% light (nom.)	instant full light
Power factor (nom.)	1
Voltage (Nom)	12 V
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy efficiency label (EEL)	B
Energy Consumption kWh/1000 h	48 kWh
Luminaire Design Requirements	
Bulb temperature (max.)	410 °C
Cap base temperature (max.)	410 °C
Product Data	
Full product code	871150042444071
Order product name	MASTERLine ES 45W GU5.3 12V 36D 1CT/4X5F
EAN/UPC – product	8711500424440
Order code	42444071
Numerator – quantity per pack	1
Numerator – packs per outer box	20
Material no. (12NC)	924896117101

# MASTERLine ES

Net weight (piece)	30.000 g
ILCOS Code	HRGS-45-12-GU5.3-50/36

## Dimensional drawing



MLES 18144 45W GU5.3 12V MR16 36D

Product	D (max)	C1 (max)
MASTERLine ES 45W GU5.3 12V 36D 1CT/4X5F	51 mm	50.5 mm

## Photometric data

