



Energy Advantage IR MR16

35MRC16/IRC/ALU/FL36 20PK

Philips Energy Advantage IRC MR16 lamps make it easy to optimize the look and feel of your merchandise, and the shoppers experience, with lower operating costs.

Product data

General Information	
Base	GU5.3 [GU5.3]
Operating Position	Universal [Universal]

Light Technical	
Beam Angle (Nom)	36 °
Luminous Intensity (Max)	2200 cd
Correlated Color Temperature (Nom)	3000 K
Color Rendering Index (Nom)	100


Operating and Electrical	
Power (Rated) (Nom)	35 W
Lamp Current (Nom)	2.92 A
Starting Time (Nom)	0.0 s
Voltage (Nom)	12 V

Luminaire Design Requirements	
Bulb Temperature (Max)	250 °C
Cap-Base Temperature (Max)	380 °C

Product Data	
XUCDM.COPY.Product.Title	EnAdvIR Alu 35W 12V MR16 36D 1CT/4XF5
EAN/UPC - Product	046677202682
Order code	202689
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material Nr. (12NC)	925633717104
Net Weight (Piece)	32.000 g
ILCOS Code	HRGS-35-12-GU5.3-50/36


Energy Advantage IR MR16

Dimensional drawing



MLES Alu 35W GU5.3 12V MR16 36D


Product	D (max)	C1 (max)
EnAdvIR Alu 35W 12V MR16 36D 1CT/4XF5	51 mm	50.5 mm



MLES Alu 35W GU5.3 12V MR16 36D

Product	D (max)	C1 (max)
EnAdvIR Alu 35W 12V MR16 36D 1CT/4XF5	51 mm	50.5 mm

Photometric data



Energy Advantage IR MR16

