



# Halogen Classic Candle B35

## Halogen Classic 28W E14 230V B35 2CT/12X5F

Philips Halogen Classic Candle light bulbs offer the classical shape you are used to. This new 'classic' gives high-quality light, is dimmable and starts immediately.


#### **Product data**

General Information	
Cap-Base	E14 [E14]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 hour(s)
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 hour(s)
Lighting Technology	Halogen
Light Technical	
Luminous Flux	370 lm
Correlated Color Temperature (Nom)	2800 K
Luminous Efficacy (rated) (Nom)	12.4 lm/W
Color rendering index (CRI)	100
Operating and Electrical	
Power Consumption	28.0 W
Lamp Current (Nom)	0.12 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	230 V
Voltage (Nom)	230 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	B35 [B 35mm]
Approval and Application	
Energy Consumption kWh/1000 h	28 kWh
Product Data	
Order product name	Halogen 28W E14 230V B35 2CT/12X5F
Full product name	Halogen Classic 28W E14 230V B35 2CT/12X5F
Full product code	871829115830100
Order code	15830100
Material Nr. (12NC)	925639644243
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291158301
Numerator - Packs per outer box	60
EAN/UPC - Case	8718291158325

### Halogen Classic Candle B35

#### Dimensional drawing



Product	D (max)	C (max)
Halogen 28W E14 230V B35 2CT/12X5F	36 mm	99.2 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 29 - data subject to change