PHILIPS Lighting



Halogen Clickline G9

Halogen Capsule 28W G9 240V 1BC/15 SRP

Ideal solution for small decorative luminaires. UV-block glass and safety fuse allow usage without cover glass. The compact Clickline gives crisp white light over a long lifetime.


Product data

General Information				
Cap-Base	G9 [G9]			
Operating Position	UNIVERSAL [Any or Universal (U)]			
Switching Cycle	8,000			
Rated Lifetime (Hours)	2,000 hour(s)			
Lighting Technology	Halogen			
Light Technical				
Luminous Flux	370 lm			
Correlated Color Temperature (Nom)	2800 K			
Luminous Efficacy (rated) (Nom)	12.1 lm/W			
Color rendering index (CRI)	100			
Operating and Electrical				
Power Consumption	28 W			
Lamp Current (Nom)	0.12 A			
Warm-up time to 60% light	instant full light s			
Power Factor (Fraction)	1			
Voltage (Nom)	240 V			
Voltage (Nom)	240 V			

Controls and Dimming			
Dimmable	Yes		
Mechanical and Housing			
Bulb Finish	Clear		
Bulb Shape	T13 [T 13 mm]		
Product Data			
Order product name	Halogen Capsule 28W G9 240V 1BC/15 SRP		
Full product name	Halogen Capsule 28W G9 240V 1BC/15 SRP		
Full product code	872790025289701		
Order code	925640645506		
Material Nr. (12NC)	925640645506		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8727900252897		
Numerator - Packs per outer box	15		
EAN/UPC - Case	8718291229476		

Halogen Clickline G9

Dimensional drawing



Product	D (max)	L	C (max)
Halogen Capsule 28W G9 240V 1BC/15 SRP	12.75 mm	21.7 mm	44.6 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, September 4 - data subject to change