



Halogen Classic Candle B35

ClassicHalo 28W B15 240V B35 CL 2PF

Philips Halogen Classic Candle light bulbs offer the classical shape you are used to. This new 'classic' gives high-quality light, is dimmable and starts immediately.

Product data

General Information	
Cap-Base	B15 [B15]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 hour(s)
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 hour(s)
Lighting Technology	Halogen
Light Technical	
Luminous Flux	370 lm
Correlated Color Temperature (Nom)	2800 K
Luminous Efficacy (rated) (Nom)	12.4 lm/W
Color rendering index (CRI)	100
Operating and Electrical	
Power Consumption	28.0 W
Lamp Current (Nom)	0.12 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	240 V
Voltage (Nom)	240 V

Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Bulb Finish	Clear	
Bulb Shape	B35 [B 35mm]	
Approval and Application		
Energy Consumption kWh/1000 h	28 kWh	
Product Data		
Order product name	ClassicHalo 28W B15 240V B35 CL 2PF	
Full product name	ClassicHalo 28W B15 240V B35 CL 2PF	
Full product code	871829121972900	
Order code	925712345502	
Material Nr. (12NC)	925712345502	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8718291219729	
Numerator - Packs per outer box	70	
EAN/UPC - Case	8718291219743	

Halogen Classic Candle B35

Dimensional drawing

Product	D (max)	C (max)
ClassicHalo 28W B15 240V B35 CL 2PF	36 mm	97 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, September 4 - data subject to change