



Brilliantline Dichroic

Brilliantline Dichroic EC 35W GU4 12V 30D 1CT/10X5F

Superior-quality low-voltage halogen burner in glass reflector. Ideal solution for small decorative luminaires, putting your objects in the spotlight. Dichroic coating prevents heat transmission onto the object.


Product data

General Information	
Cap-Base	GU4 [GU4]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	4,000 hour(s)
Switching Cycle	16,000
Rated Lifetime (Hours)	4,000 hour(s)
Lighting Technology	Halogen
Light Technical	
Beam Angle (Nom)	30 degree(s)
Correlated Color Temperature (Nom)	3000 K
Color rendering index (CRI)	100
Luminous Flux in 90° Cone (Rated)	430 lm
Operating and Electrical	
Power Consumption	35 W
Lamp Current (Nom)	2.9 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	Instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	12 V
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	MR11 [1.375inch/35mm]
Approval and Application	
Energy Consumption kWh/1000 h	37 kWh
Product Data	
Order product name	Brill EC 35W GU4 12V 30D 1CT/10X5F
Full product name	Brilliantline Dichroic EC 35W GU4 12V 30D 1CT/10X5F
Full product code	871869959139700
Order code	59139700
Material Nr. (12NC)	925721517102
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699591397
Numerator - Packs per outer box	50
EAN/UPC - Case	8718699591403

Brilliantline Dichroic

Dimensional drawing



Product	D (max)	C (max)
Brill EC 35W GU4 12V 30D 1CT/10X5F	35 mm	40 mm

