



Brilliantline Dichroic

Brilliantline Dichroic EC 20W GU4 12V 30D 1CT/10X5F

Low-voltage, xenon gas-filled halogen burner with axial filament optically positioned in a glass reflector


Product data

General Information	
Cap base	GU4 [GU4]
Operating position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	4,000 h
Switching Cycle	16,000
Rated Lifetime (Hours)	4,000 h
Lighting Technology	Halogen
Light Technical	
Beam angle (nom.)	30 degree(s)
Correlated Colour Temperature	3000 K
Colour rendering index (CRI)	100
Luminous flux in 90° cone (rated)	205 lm
Operating and Electrical	
Power Consumption	20 W
Lamp current (nom.)	1.7 A
Starting time (nom.)	0.0 s
Warm-up time to 60% light	Instant full light s
Power Factor (Fraction)	1
Voltage (nom.)	12 V
Voltage (nom.)	12 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Lamp Finish	Clear
Bulb shape	MR11 [1.375 inch/35 mm]
Approval and Application	
Energy consumption kWh/1,000 hours	21 kWh
Product Data	
Order product name	Brill EC 20W GU4 12V 30D 1CT/10X5F
Full product name	Brilliantline Dichroic EC 20W GU4 12V 30D 1CT/10X5F
Full EOC	871869959137300
Order code	59137300
Material no. (12 NC)	925721617102
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718699591373
Numerator – packs per outer box	50
EAN/UPC - Case	8718699591380

Brilliantline Dichroic

Dimensional drawing



Product	D (max)	C (max)
Brill EC 20W GU4 12V 30D 1CT/10X5F	35 mm	40 mm

