



Standard Candle B35 frosted

Stan 40W E14 230V B35 FR 1CT/10X10F

Flame-shaped bulb with inside-frosted glass and vacuum- or gas-filled bulb with B- or E-base $\,$

Product data


General Information Cap-Base E14 [E14] Operating Position UNIVERSAL [Any or Universal (U)] Nominal lifetime 1,000 hour(s) Rated Lifetime (Hours) 1,000 hour(s) Lighting Technology Incandescent Light Technical Luminous Flux 410 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming Dimmable Yes		
Operating Position UNIVERSAL [Any or Universal (U)] Nominal lifetime 1,000 hour(s) Rated Lifetime (Hours) Lighting Technology Incandescent Light Technical Luminous Flux Color rendering index (CRI) Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Controls and Dimming	General Information	
Nominal lifetime 1,000 hour(s) Rated Lifetime (Hours) 1,000 hour(s) Lighting Technology Incandescent Light Technical Luminous Flux 410 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Cap-Base	E14 [E14]
Rated Lifetime (Hours) Lighting Technology Incandescent Light Technical Luminous Flux 410 lm Color rendering index (CRI) Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Controls and Dimming	Operating Position	UNIVERSAL [Any or Universal (U)]
Lighting Technology Incandescent Light Technical Luminous Flux 410 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Nominal lifetime	1,000 hour(s)
Light Technical Luminous Flux 410 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Rated Lifetime (Hours)	1,000 hour(s)
Luminous Flux 410 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Lighting Technology	Incandescent
Luminous Flux 410 lm Color rendering index (CRI) 100 Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming		
Color rendering index (CRI) 100 Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Light Technical	
Operating and Electrical Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Luminous Flux	410 lm
Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Color rendering index (CRI)	100
Power Consumption 40 W Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming		
Voltage (Nom) 230 V Voltage (Nom) 230 V Controls and Dimming	Operating and Electrical	
Voltage (Nom) 230 V Controls and Dimming	Power Consumption	40 W
Controls and Dimming	Voltage (Nom)	230 V
	Voltage (Nom)	230 V
Dimmable Yes	Controls and Dimming	
	Dimmable	Yes

Mechanical and Housing		
Bulb Finish	Frosted	
Bulb Shape	B35 [B 35mm]	
Product Data		
Order product name	Stan 40W E14 230V B35 FR 1CT/10X10F	
Full product name	Stan 40W E14 230V B35 FR 1CT/10X10F	
Full product code	871869658984700	
Order code	926000006933	
Material Nr. (12NC)	926000006933	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8718696589847	
Numerator - Packs per outer box	100	
EAN/UPC - Case	8718696589861	

Datasheet, 2023, October 16 data subject to change

Standard Candle B35 frosted

Dimensional drawing



Product	D	C (max)
Stan 40W E14 230V B35 FR 1CT/10X10F	35 mm	100 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.