



U-Bent Rapid Start T8

FB31T8/TL835/ALTO 15/1

Philips leads the industry with the lowest level mercury technology. Reducing the mercury level (source reduction) during the manufacturing phase is essential to creating products that are less harmful to the environment.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Features	ALTO® (ALTO)
Light Technical	
Color Code	TL835 [CCT of 3500K (835)]
Luminous Flux	2,750 lm
Color Designation	TL835
Correlated Color Temperature (Nom) 4100 K	
Color rendering index (CRI)	85
Operating and Electrical	
Power Consumption	31 W
Mechanical and Housing	

Bulb Shape

T8-1-5/8U [U-bent T 1inch with 1-5/8" leg spacing]

Approval and Application	
Energy Saving Product	Energy Saving
Mercury (Hg) Content (Nom)	3.0 mg
Product Data	
Order product name	FB31T8/TL835/ALTO 15/1
Full product name	FB31T8/TL835/ALTO 15/1
Order code	226720
Material Nr. (12NC)	927861283502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677226725
Numerator - Packs per outer box	15
EAN/UPC - Case	50046677226720

U-Bent Rapid Start T8

Dimensional drawing

Product

FB31T8/TL835/ALTO 15/1





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 17 - data subject to change