



T12 Standard

TL-RS 40W/54-765 30PK 30/1

Low-pressure mercury discharge lamps with a tubular 37 mm envelope

Product data

| General Information | |
|------------------------------------|---------------------------------|
| Cap-Base | G13 [Medium Bi-Pin Fluorescent] |
| | |
| Light Technical | |
| Color Code | 54-765 |
| Luminous Flux | 2,600 lm |
| Color Designation | Daylight |
| Correlated Color Temperature (Nom) | 6500 K |
| Color rendering index (CRI) | 73 |
| | |
| Operating and Electrical | |
| Power Consumption | 40 W |
| | |
| Mechanical and Housing | |
| Bulb Shape | T-12 (T12) |

| Approval and Application | |
|---------------------------------|----------------------------|
| Mercury (Hg) Content (Nom) | 4.4 mg |
| | |
| Product Data | |
| Order product name | TL-RS 40W/54-765 30PK 30/1 |
| Full product name | TL-RS 40W/54-765 30PK 30/1 |
| Order code | 226480 |
| Material Nr. (12NC) | 927888005406 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 046677226480 |
| Numerator - Packs per outer box | 30 |
| EAN/UPC - Case | 50046677226485 |
| | |


Datasheet, 2023, May 1 data subject to change

T12 Standard

Dimensional drawing

Product

TL-RS 40W/54-765 30PK 30/1





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.