



MASTER PL-C 4 Pin

MASTER PL-C 13W/827/4P 1CT/5X10BOX

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 4 parallel narrow fluorescent tubes

Product data

General Information	
Cap base	G24Q-1 [G24q-1]
Life to 50% failures preheat (nom.)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %
Light Technical	
Colour code	827 [CCT of 2,700 K]
Luminous flux (nom.)	925 lm
Luminous flux (rated) (nom.)	925 lm
Colour designation	Incandescent White
Correlated colour temperature (nom.)	2700 K
Luminous efficacy (rated) (nom.)	69 lm/W
Color rendering index (nom.)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %
Operating and Electrical	
Power (Rated) (Nom)	13.0 W
Lamp current (nom.)	0.170 A


Temperature	
Design temperature (nom.)	28 °C
Controls and Dimming	
Dimmable	yes
Mechanical and Housing	
Cap base information	4P
Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	1.4 mg
Energy Consumption kWh/1000 h	15 kWh
Product Data	
Full product code	871150062326370
Order product name	MASTER PL-C 13W/827/4P 1CT/5X10BOX
EAN/UPC – product	8711500623263
Order code	62326370
Local Code	13PLC8274PIN
Numerator – quantity per pack	1
Numerator – packs per outer box	50
Material no. (12NC)	927907182740
Net weight (piece)	49.900 g
ILCOS Code	FSQ-13/27/1B-E-G24q=1

MASTER PL-C 4 Pin

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 13W/827/4P 1CT/5X10BOX	27.1 mm	27.1 mm	97.5 mm	117.0 mm	131.9 mm

PL-C 13W/827/4P

Photometric data



Lightcolour /827



Lightcolour /827

MASTER PL-C 4 Pin

Lifetime

