



# MASTER PL-C 4 Pin

## MASTER PL-C 18W/865/4P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General information	
Cap-Base	G24Q-2 [ G24q-2]
Life to 50% Failures Preheat (Nom)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %
Light technical	
Color Code	865 [ CCT of 6500K]
Luminous Flux (Nom)	1120 lm
Luminous Flux (Rated) (Nom)	1120 lm
Color Designation	Cool Daylight

Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	62.3 lm/W
Color Rendering Index (Nom)	80
LLMF 2000 h Rated	90 %
LLMF 4000 h Rated	85 %
LLMF 6000 h Rated	81 %
LLMF 8000 h Rated	77 %
Operating and electrical	
Power (Nom)	18.0 W
Lamp Current (Nom)	0.230 A

# MASTER PL-C 4 Pin

## Temperature

Design Temperature (Nom)	28 °C
--------------------------	-------

## Controls and dimming

Dimmable	Yes
----------	-----

## Mechanical and housing

Cap-Base Information	4 Pins
----------------------	--------


## Approval and application

Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	20 kWh

## Product data

Full product code	871150027704600
Order product name	MASTER PL-C 18W/865/4P 1CT/5X10BOX
EAN/UPC - Product	8711500277046
Order code	927907286501
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927907286501
Net Weight (Piece)	55.300 g


## Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 18W/865/4P 1CT/5X10BOX	27.1 mm	27.1 mm	109.5 mm	128.0 mm	142.9 mm

MASTER PL-C 18W/865/4P 1CT/5X10BOX

## Photometric data




LDPB\_PLC4P\_865-Spectral power distribution B/W



LDPO\_PLC4P\_865-Spectral power distribution Colour


# MASTER PL-C 4 Pin

## Lifetime



LDLE\_PLC4P\_0001-Life expectancy diagram

LDLE\_PLC4P\_0002-Life expectancy diagram



LDLM\_PLC4P\_0001-Lumen maintenance diagram

