



PL-T Triple 4-Pin Base

PL-T 26W/835/A/4P/ALTO

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum efficiency and sleek design solutions are required.

Product data

General Information		LLMF 12000 h Rated	
Base	GX24Q-3 [GX24q-3]		81 %
LSF Preheat 2000 h Rated	99 %	Operating and Electrical	
LSF Preheat 4000 h Rated	98 %	Power (Rated) (Nom)	27.0 W
LSF Preheat 6000 h Rated	97 %	Lamp Current (Nom)	0.335 A
LSF Preheat 8000 h Rated	90 %	Temperature	
Light Technical		Design Temperature (Nom)	28 °C
Color Code	835 [CCT of 3500K]	Controls and Dimming	
Initial lumen (Nom)	1750 lm	Dimmable	Yes
Luminous Flux (Rated) (Nom)	1750 lm	Mechanical and Housing	
Color Designation	White (WH)	Cap-Base Information	4P
Correlated Color Temperature (Nom)	3500 K	Approval and Application	
Luminous Efficacy (rated) (Nom)	64.8 lm/W	Energy Efficiency Label (EEL)	B
Color Rendering Index (Nom)	82	Mercury (Hg) Content (Nom)	1.4 mg
LLMF 2000 h Rated	92 %		
LLMF 4000 h Rated	88 %		
LLMF 6000 h Rated	85 %		
LLMF 8000 h Rated	84 %		

PL-T Triple 4-Pin Base

Product Data


Order product name	PL-T 26W/835/A/4P/ALTO
EAN/UPC - Product	046677268244
Order code	458265
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10

Material Nr. (12NC)	927910983550
Net Weight (Piece)	64.000 g
ILCOS Code	FSM-26/35/1B-E-GX24q=3

Warnings and Safety

• Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050


Dimensional drawing




PL-T ALTO 26W/835/4P A

Product	D (max)	A (max)	B (max)	C (max)
PL-T 26W/835/A/4P/ALTO	41 mm	86.7 mm	111.0 mm	126.7 mm

Photometric data



Lightcolor /835




Lightcolor /835

PL-T Triple 4-Pin Base

Lifetime



Lumen Maintenance 3 h and 12 h cycle



Life Expectancy 3 h cycle

Life Expectancy 12 h cycle

