

MASTER PL-T 4 Pin
4-針腳型

MASTER PL-T 42W/840/4P 1CT/5X10BOX

省電型精巧螢光燈管。精巧型長電弧低壓水銀放電燈管。套管內含 6 個平行細長螢光燈管

安全提示

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般資訊	
燈座基底	GX24Q-4 [GX24q-4]
通量測量參考	Sphere

照明技術	
色碼	840 [CCT of 4000K]
光通量	3,100 lm
色彩名稱	冷白光 (CW)
色度坐標 X (標稱)	0.38
色度坐標 Y (Nom)	0.38
相關色彩溫度 (規範)	4000 K
流明功能 (額定) (最小)	74 lm/W
演色性指數 (CRI)	80

運轉與電力	
耗電量	42.0 W
燈具電流 (標稱)	0.320 A

控制與調光	
可調光	是

認證與應用	
節能省電等級	G
汞 (Hg) 含量 (最大)	1.4 mg
汞 (Hg) 含量 (標稱)	1.4 mg
能源消耗 kWh/1000 h	42 kWh
EPREL 註冊碼	423354


產品資料	
下訂產品名稱	MASTER PL-T 42W/840/4P 1CT/5X10BOX
完整產品名稱	MASTER PL-T 42W/840/4P 1CT/5X10BOX
完整產品代碼	871150061137670

MASTER PL-T 4 Pin 4-針腳型

訂單代碼	927914884071
材質 Nr. (12NC)	927914884071
分子 - 每個包裝的數量	1
EAN/UPC - 產品/案例	8711500611376


分子 - 每一外盒包裝	50
EAN/UPC - 箱	8711500611390

二维绘图




Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T 42W/840/4P 1CT/5X10BOX	41.0 mm	120.7 mm	145.0 mm	160.7 mm

光度数据




Spectral Power Distribution Colour - MASTER PL-T 42W/840/4P 1CT/5X10BOX

壽命




Life Expectancy Diagram - MASTER PL-T 42W/840/4P 1CT/5X10BOX



Life Expectancy Diagram - MASTER PL-T 42W/840/4P 1CT/5X10BOX

MASTER PL-T 4 Pin 4-針腳型

壽命



Lumen Maintenance Diagram - MASTER PL-T 42W/840/4P 1CT/5X10BOX

© 2023 Signify Holding 保留一切權利。 Signify 不對本協議所含括資訊之準確性及完整性提供任何聲明或保證，對以此訊息為依據採取的任何行動亦概不負責。 除非 Signify 同意，本文件提及之資訊並非任何商業合約，亦不構成任何報價或合約任一部分。
Philips 與 Philips Shield Emblem 均屬 Koninklijke Philips N.V 註冊商標。