



MASTER TL-D Super 80



MASTER TL-D Super 80 36W/827 1SL/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information					
Cap-Base	G13 [Medium Bi-Pin Fluorescent]				
Flux measurement reference	Sphere				
Life to 50% Failures (Nom)	15,000 hour(s)				
Light Technical					
Color Code	827 [CCT of 2700K]				
Luminous Flux	3,350 lm				
Color Designation	Incandescent White				
Chromaticity Coordinate X (Nom)	0.463				
Chromaticity Coordinate Y (Nom)	0.42				
Correlated Color Temperature (Nom)	2700 K				
Luminous Efficacy (rated) (Nom)	93 lm/W				
Color rendering index (CRI)	82				
Operating and Electrical					
Power Consumption	36.8 W				

Lamp Current (Nom)	0.440 A			
Controls and Dimming				
Dimmable	Yes			
Mechanical and Housing				
Bulb Shape	Т8			
Approval and Application				
Energy Efficiency Class	G			
Mercury (Hg) Content (Nom)	1.7 mg			
Energy Consumption kWh/1000 h	37 kWh			
EPREL Registration Number	423377			
Product Data				
Order product name	MASTER TL-D Super 80 36W/827 1SL/25			
Full product name	MASTER TL-D Super 80 36W/827 1SL/25			


Datasheet, 2024, March 11 data subject to change

MASTER TL-D Super 80

Full product code	871150063192340
Order code	927921082723
Material Nr. (12NC)	927921082723
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500631923


Numerator - Packs per outer box	25	
EAN/UPC - Case	8711500631930	

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80	28 mm	1,199.4 mm	1,206.5 mm	1,204.1 mm	1,213.6 mm
36W/827 1SL/25					


Photometric data



Spectral Power Distribution Colour - MASTER TL-D Super 80 36W/827 1SL/25

Lifetime






Life Expectancy Diagram - MASTER TL-D Super 80 36W/827 1SL/25

Life Expectancy Diagram - MASTER TL-D Super 80 36W/827 1SL/25

MASTER TL-D Super 80

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 36W/827 1SL/25

