



MASTER TL5 High Efficiency

MASTER TL5 HE 14W/830 UNP/40

This TL5 lamp (tube diameter 16 mm) has a high luminous efficacy, resulting in low energy consumption. The High Efficiency TL5 lamp offers excellent lumen maintenance and good color rendering. Application areas are offices, industry, public and governmental buildings, schools, hospitals and indoor sports lighting.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	G5 [G5]			
Features	na [Not Applicable]			
Flux measurement reference	Sphere			
Light Technical				
Color Code	830 [CCT of 3000K]			
Luminous Flux	1,200 lm			
Color Designation	Warm White (WW)			
Chromaticity Coordinate X (Nom)	0.44			
Chromaticity Coordinate Y (Nom)	0.403			
Correlated Color Temperature (Nom)	3000 K			
Luminous Efficacy (rated) (Nom)	86 lm/W			
Color rendering index (CRI)	82			

Operating and Electrical				
Power Consumption	14.0 W			
Lamp Current (Nom)	0.165 A			
Controls and Dimming				
Dimmable	Yes			
Mechanical and Housing				
Bulb Shape	T5 [16 mm (T5)]			
Approval and Application				
Energy Efficiency Class	G			
Mercury (Hg) Content (Nom)	1.2 mg			
Energy Consumption kWh/1000 h	14 kWh			
EPREL Registration Number	423441			


Datasheet, 2023, April 17 data subject to change

MASTER TL5 High Efficiency

Product Data	
Order product name	MASTER TL5 HE 14W/830 UNP/40
Full product name	MASTER TL5 HE 14W/830 UNP/40
Full product code	871150061063855
Order code	61063855
Material Nr. (12NC)	927926083018


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500610638
Numerator - Packs per outer box	40
EAN/UPC - Case	8711500634283

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE 14W/830	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
UNP/40					


Photometric data



Spectral Power Distribution Colour - MASTER TL5 HE 14W/830 UNP/40

Lifetime






Life Expectancy Diagram - MASTER TL5 HE 14W/830 UNP/40

Life Expectancy Diagram - MASTER TL5 HE 14W/830 UNP/40

MASTER TL5 High Efficiency

Lifetime



Lumen Maintenance Diagram - MASTER TL5 HE 14W/830 UNP/40



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.