



MASTER TL5 High Output

MASTER TL5 HO 39W/840 SLV/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Product data

General Information		LLMF 2000 h Rated		96 %	
Cap base	G5 [G5]	LLMF 4000 h Rated	95 %		
Life to 50% failures preheat (nom.)	30000 h	LLMF 6000 h Rated	94 %		
Features	na [Not Applicable]	LLMF 8000 h Rated	93 %		
System description	High Output (HO)	LLMF 12000 h Rated	92 %		
LSF Preheat 2000 h Rated	99 %	LLMF 16000 h Rated	91 %		
LSF Preheat 4000 h Rated	99 %	LLMF 20000 h Rated	90 %		
LSF Preheat 6000 h Rated	99 %	Operating and Electrical			
LSF Preheat 8000 h Rated	99 %	Power (Rated) (Nom)	38.0 W		
LSF Preheat 16000 h Rated	97 %	Lamp current (nom.)	0.325 A		
LSF Preheat 20000 h Rated	84 %	Temperature			
Light Technical		Design temperature (nom.)	35 °C		
Colour Code	840 [CCT of 4,000 K]	Controls and Dimming			
Lamp Luminous Flux 25°C EL (Nom)	3500 lm	Dimmable	yes		
Lamp Luminous Flux (Nom)	3100 lm	Mechanical and Housing			
Colour Designation	Cool White (CW)	Cap base information	Green Plate		
Luminous efficacy (@ max. lumen, rated) (nom.)	92 lm/W	Approval and Application			
Colour Temperature, horizontal (Nom)	4000 K	Energy efficiency label (EEL)	A+		
Lamp Luminous Efficacy EM (Nom)	82 lm/W				
Colour Rendering Index,horiz (Max)	85				
Colour Rendering Index,horiz (Min)	80				
Colour Rendering Index,horiz (Nom)	82				

MASTER TL5 High Output


Mercury (Hg) content (nom.)	1.4 mg
Energy Consumption kWh/1000 h	42 kWh
Product Data	
Full product code	871150063964655
Order product name	MASTER TL5 HO 39W/840 SLV/40
EAN/UPC – product	8711500639646
Order code	927928584055

Numerator – quantity per pack	1
Numerator – packs per outer box	40
Material no. (12NC)	927928584055
Net weight (piece)	79.200 g
ILCOS Code	FDH-39/40/1B-L/P-G5-16/850

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO 39W/840 SLV/40	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm

TL5 HO 39W/840

Photometric data



Lightcolour /840



Lightcolour /840

MASTER TL5 High Output

Lifetime

