



PL-T Triple 4-Pin Base Non Amalgam

PL-T 26W/835/4P/ALTO

Philips Non-Amalgam PL-T Compact Fluorescent lamps offer designers, specifiers, and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities.

Product data


General Information			
Cap-Base	GX24Q-3 [GX24q-3]		
Light Technical			
Color Code	835 [CCT of 3500K]		
Luminous Flux	1,750 lm		
Color Designation	White (WH)		
Correlated Color Temperature (Nom)	3500 K		
Luminous Efficacy (Rated) (Min)	67.3 lm/W		
Luminous Efficacy (rated) (Nom)	65.1 lm/W		
Color rendering index (CRI)	82		
Operating and Electrical			
Power Consumption	26 W		
Lamp Current (Nom)	0.335 A		
Controls and Dimming			
Dimmable	Yes		

Approval and Application			
Mercury (Hg) Content (Nom)	1.4 mg		
Energy Consumption kWh/1000 h	29 kWh		
Product Data			
Order product name	PL-T 26W/835/4P/ALTO		
Full product name	PL-T 26W/835/4P/ALTO		
Order code	433391		
Material Nr. (12NC)	927933083530		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	046677433390		
Numerator - Packs per outer box	10		
EAN/UPC - Case	50046677433395		

Datasheet, 2023, May 1 data subject to change


PL-T Triple 4-Pin Base Non Amalgam

Dimensional drawing




Product	D (max)	A (max)	B (max)	C (max)
PL-T 26W/835/4P/ALTO	41.0 mm	86.7 mm	111.0 mm	126.7 mm


Photometric data



Spectral Power Distribution Colour - PL-T 26W/835/4P/ALTO

Lifetime






Life Expectancy Diagram - PL-T 26W/835/4P/ALTO

Life Expectancy Diagram - PL-T 26W/835/4P/ALTO

PL-T Triple 4-Pin Base Non Amalgam

Lifetime



Lumen Maintenance Diagram - PL-T 26W/835/4P/ALTO

