PHILIPS Lighting



MASTER PL-S 2 Pin

MASTER PL-S 7W/830/2P 1CT/5X10BOX

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- \cdot Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Luminous Efficacy (rated) (Nom)	57 lm/W
Cap-Base	G23 [G23]	Color rendering index (CRI)	82
Flux measurement reference	Sphere		
Life to 50% Failures (Nom)	10,000 hour(s)	Operating and Electrical	
		Power Consumption	7.2 W
Light Technical		Lamp Current (Nom)	0.175 A
Color Code	830 [CCT of 3000K]		
Luminous Flux	400 lm	Controls and Dimming	
Color Designation	Warm White (WW)	Dimmable	No
Chromaticity Coordinate X (Nom)	0.44		
Chromaticity Coordinate Y (Nom)	0.403	Approval and Application	
Correlated Color Temperature (Nom)	3000 K	Energy Efficiency Class	G

MASTER PL-S 2 Pin

Mercury (Hg) Content (Max)	1.4 mg		
Mercury (Hg) Content (Nom)	1.4 mg		
Energy Consumption kWh/1000 h	8 kWh		
EPREL Registration Number	423584		
Product Data			
Order product name	MASTER PL-S 7W/830/2P 1CT/5X10BOX		
Full product name	MASTER PL-S 7W/830/2P 1CT/5X10BOX		
Full product code	871150026062870		


Order code	26062870
Material Nr. (12NC)	927935683011
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500260628
Numerator - Packs per outer box	50
EAN/UPC - Case	8711500260642

Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-S 7W/830/2P 1CT/5X10BOX	28 mm	13 mm	97 mm	113 mm	135 mm


Photometric data



Spectral Power Distribution Colour - MASTER PL-S 7W/830/2P 1CT/5X10BOX

MASTER PL-S 2 Pin

Lifetime



Life Expectancy Diagram - MASTER PL-S 7W/830/2P 1CT/5X10BOX

~	1 1

Lumen Maintenance Diagram - MASTER PL-S 7W/830/2P 1CT/5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 16 - data subject to change

Life Expectancy Diagram - MASTER PL-S 7W/830/2P 1CT/5X10BOX