



MASTER PL-S 2 Pin

MASTER PL-S 9W/865/2P 1CT/10

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base

Product data

General Information	
Cap base	G23 [G23]
Life to 50% failures (nom.)	10000 h
Light Technical	
Colour Code	865 [CCT of 6500K]
Lamp Luminous Flux 25°C EL (Nom)	540 lm
Colour Designation	Cool Daylight
Lumen maintenance 2,000 hours (nom.)	91 %
Lumen maintenance 5,000 hours (nom.)	87 %
Colour Temperature, horizontal (Nom)	6500 K
Lamp Luminous Efficacy EM (Nom)	62 lm/W
Colour Rendering Index, horiz (Nom)	82
Operating and Electrical	
Power (Rated) (Nom)	8.6 W
Lamp current (nom.)	0.170 A
Voltage (Nom)	60 V
Controls and Dimming	
Dimmable	No


Mechanical and Housing	
Cap base information	2P
Approval and Application	
Energy efficiency label (EEL)	A
Product Data	
Full product code	871869960704300
Order product name	MASTER PL-S 9W/865/2P 1CT/10
EAN/UPC – product	8718699607043
Order code	927936086565
Numerator – quantity per pack	1
Numerator – packs per outer box	10
Material no. (12NC)	927936086565
Net weight (piece)	32.000 g

MASTER PL-S 2 Pin

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.



Dimensional drawing





Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-S 9W/865/2P 1CT/10	28 mm	13 mm	97 mm	113 mm	135 mm

PL-S 9W/865/2P LM

Photometric data



Lifetime



MASTER PL-S 2 Pin

Lifetime

