



PL-Q 4 Pin

PL-Q 16W/827/4P 1CT/10

Compact fluorescent lamps with a quadrant-like shape

Product data

General Information	
Cap base	GR10Q [GR10q]
Life to 50% failures preheat (nom.)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	95 %
LSF Preheat 8000 h Rated	89 %
LSF Preheat 16000 h Rated	22 %
LSF Preheat 20000 h Rated	4 %
Light Technical	
Colour code	827 [CCT of 2,700 K]
Luminous flux (nom.)	1050 lm
Luminous flux (rated) (nom.)	1050 lm
Colour designation	Incandescent White
Correlated colour temperature (nom.)	2700 K
Luminous efficacy (rated) (nom.)	66.6 lm/W
Color rendering index (nom.)	82
LLMF 2000 h Rated	90 %
LLMF 4000 h Rated	86 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	80 %
LLMF 12000 h Rated	79 %
LLMF 16000 h Rated	78 %
LLMF 20000 h Rated	78 %

Operating and Electrical	
Power (Rated) (Nom)	16.0 W
Lamp current (nom.)	0.195 A
Temperature	
Design temperature (nom.)	25 °C
Controls and Dimming	
Dimmable	yes
Mechanical and Housing	
Cap base information	4P
Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	4 mg
Energy Consumption kWh/1000 h	18 kWh
Product Data	
Full product code	871150026988125
Order product name	PL-Q 16W/827/4P 1CT/10BOX
EAN/UPC – product	8711500269881
Order code	26988125
Local Code	16PLQ8274PIN
Numerator – quantity per pack	1
Numerator – packs per outer box	10


PL-Q 4 Pin

Material no. (12NC)	927939182740
Net weight (piece)	68.000 g
ILCOS Code	FSS-16/27/1B-E-GR10q

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




Product	U (max)	D (max)	D1 (max)	C (max)	C1 (max)	F (max)	E (max)
PL-Q 16W/ 827/4P 1CT/ 10BOX	40 mm	13.7 mm	27.5 mm	138 mm	49 mm	40.5 mm	135 mm

PL-Q 16W/827/4P

Photometric data



Lightcolour /827



Lightcolour /827

PL-Q 4 Pin

Lifetime

