



MASTER TL5 Circular

MASTER TL5 CIRCULAR 55W/840 1CT/10

This circular TL5 lamp (tube diameter 16 mm) offers extended design possibilities. The slim tube allows the creation of extremely flat luminaires and enables omnidirectional light distribution. It is suitable for a wide range of professional and semi-professional applications, and is ideal for use in shops, offices and public areas with unconventional layouts.

Product data

General Information	
Cap base	G24X13 [2GX13]
Life to 50% failures preheat (nom.)	12000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	96 %
LSF Preheat 8000 h Rated	89 %
LSF Preheat 16000 h Rated	10 %
LSF Preheat 20000 h Rated	1 %

Light Technical	
Colour code	841 [CCT of 4,100 K]
Luminous flux (nom.)	4200 lm
Luminous flux (rated) (nom.)	4200 lm
Colour designation	Cool White (CW)
Correlated colour temperature (nom.)	4100 K
Luminous efficacy (rated) (nom.)	76 lm/W
Color rendering index (max.)	85
Color rendering index (min.)	80
Color rendering index (nom.)	85
LLMF 2000 h Rated	91 %
LLMF 4000 h Rated	87 %

LLMF 6000 h Rated	84 %
LLMF 8000 h Rated	81 %
LLMF 12000 h Rated	77 %
LLMF 16000 h Rated	74 %
LLMF 20000 h Rated	72 %

Operating and Electrical	
Power (Rated) (Nom)	55.0 W
Lamp current (nom.)	0.550 A

Temperature	
Design temperature (nom.)	35 °C

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	2.5 mg
Energy Consumption kWh/1000 h	61 kWh

MASTER TL5 Circular

Product Data


Full product code	871150064251625
Order product name	MASTER TL5 Circular 55W/840 ICT/10
EAN/UPC – product	8711500642516
Order code	64251625
Numerator – quantity per pack	1

Numerator – packs per outer box	10
Material no. (12NC)	927965784013
Net weight (piece)	111.000 g
ILCOS Code	FSCH-55/40/1B-L/P-2GX13-16

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.



Dimensional drawing



TL5-C 55W/840

Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
MASTER TL5 Circular 55W/840 ICT/10	18 mm	14 mm	293 mm	305 mm	260 mm	272 mm

Photometric data



Lightcolour /840

MASTER TL5 Circular

Lifetime

