



MASTER TL-D Xtreme



MASTER TL-D Xtreme 36W/865 SLV

This MASTER TL-D Xtreme lamp offers extremely long lifetime. This results in extra-low lamp cost over life. It is therefore suitable for places where lamp replacement is expensive, due to high ceilings or disturbance of operations, and applications with long burning cycles, e.g. tunnels, oil rigs, manufacturing lines. It can be operated on existing gear or dedicated HF Xtreme gear.

Warnings and Safety

- To achieve published lifetimes for 100% operation, do not dim below 30%
- When used on electromagnetic gear, it is strongly recommended to apply only Philips S10 or S10E starters (for 18W types S2 or S2E) to achieve the published lifetimes, and to install new starters when relamping.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Color rendering index (CRI)		80
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Operating and Electrical		
Flux measurement reference	Sphere	Power Consumption	36.4 W	
Life to 50% Failures (Nom)	47,000 hour(s)	Lamp Current (Nom)	0.430 A	
Light Technical		Controls and Dimming		
Color Code	865 [CCT of 6500K]	Dimmable	Yes	
Luminous Flux	3,150 lm	Mechanical and Housing		
Color Designation	Cool Daylight	Bulb Shape	T8	
Chromaticity Coordinate X (Nom)	0.313	Approval and Application		
Chromaticity Coordinate Y (Nom)	0.337	Energy Efficiency Class	G	
Correlated Color Temperature (Nom)	6500 K			
Luminous Efficacy (rated) (Nom)	88 lm/W			

MASTER TL-D Xtreme


Mercury (Hg) Content (Max)	3 mg
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	37 kWh
EPREL Registration Number	423631

Product Data

Order product name	MASTER TL-D Xtreme 36W/865 SLV
Full product name	MASTER TL-D Xtreme 36W/865 SLV
Full product code	871150089277540


Order code	927982386514
Material Nr. (12NC)	927982386514
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500892775
Numerator - Packs per outer box	25
EAN/UPC - Case	8711500892782

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Xtreme 36W/865 SLV	28 mm	1,199.4 mm	1,206.5 mm	1,204.1 mm	1,213.6 mm



Photometric data



Spectral Power Distribution Colour - MASTER TL-D Xtreme 36W/865 SLV



MASTER TL-D Xtreme

Lifetime



Life Expectancy Diagram - MASTER TL-D Xtreme 36W/865 SLV

Life Expectancy Diagram - MASTER TL-D Xtreme 36W/865 SLV



Life Expectancy Diagram - MASTER TL-D Xtreme 36W/865 SLV

Lumen Maintenance Diagram - MASTER TL-D Xtreme 36W/865 SLV

