

# MASTER TL5 High Efficiency Eco

## MASTER TL5 HE Eco 32=35W/830 UNP/40

This extremely efficient TL5 lamp (tube diameter 16 mm) saves considerable energy by simple lamp-for-lamp replacement. The TL5 HE Eco lamp offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

### Product data

General Information	
Cap-Base	G5 [ G5]
Life to 50% Failures Preheat (Nom)	25000 h
Features	na [ Not Applicable]
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %
LSF Preheat 16000 h Rated	99 %
LSF Preheat 20000 h Rated	94 %
Light Technical	
Colour Code	830 [ CCT of 3000K]
Luminous Flux (Nom)	3650 lm
Luminous Flux (Rated) (Nom)	3250 lm
Colour Designation	Warm White (WW)
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	114 lm/W
Colour Temperature, horizontal (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	103 lm/W
Colour Rendering Index horiz (Max)	85

Colour Rendering Index horiz (Min)	80
Colour Rendering Index horiz (Nom)	82
Depreciation 2000 hrs	96 %
LLMF 4000 h Rated	95 %
Depreciation 5000 hrs	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 20000 h Rated	90 %

### Operating and Electrical

Power (Rated) (Nom)	31.7 W
Lamp Current (Nom)	0.170 A

### Temperature

Design Temperature (Nom)	35 °C
--------------------------	-------

### Controls and Dimming

Dimmable	Yes
----------	-----

# MASTER TL5 High Efficiency Eco


Approval and Application	
Energy Efficiency Label	A+
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	35 kWh
Product Data	
Full product code	872790082592300
Order product name	MASTER TL5 HE Eco 32=35W/830 UNP/40

EAN/UPC - Product	8711500880024
Order code	82592300
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40
Material Nr. (12NC)	927991183031
Net Weight (Piece)	127.400 g
ILCOS Code	FDH-32/30/1B-L/P-G5-16/1450

## Warnings and Safety

- A reduction in energy consumption is only achieved with current-controlled gear.
- The lamps operate perfectly with power-controlled gear, but in that case the light output can be up to 10% higher.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


## Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE Eco 32=35W/830 UNP/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm

## TL5 HE Eco 32=35W/830

## Photometric data





## Lightcolour /830



## Lightcolour /830


# MASTER TL5 High Efficiency Eco

## Lifetime



MASTER TL5 HE Eco Life Expectancy 3 h cycle

MASTER TL5 HE Eco Life Expectancy 12 h cycle



MASTER TL5 HE Eco Lumen Maintenance 3 h + 12 h cycle

