



# T12 Standard

## F40T12/D-765 25 PK

Low-pressure mercury discharge lamps with a tubular 37 mm envelope


### Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life to 50% Failures (Nom)	13,000 hour(s)
Light Technical	
Color Code	54-765
Luminous Flux	2,500 lm
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6200 K
Color rendering index (CRI)	75
Operating and Electrical	
Power Consumption	39.5 W
Voltage (Nom)	107 V
Voltage (Nom)	107 V
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Shape	T12
Approval and Application	
Mercury (Hg) Content (Nom)	10.5 mg
Product Data	
Order product name	F40T12/D-765 25 PK
Full product name	F40T12/D-765 25 PK
Full product code	871869667310200
Order code	928006405415
Material Nr. (12NC)	928006405415
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696673102
Numerator - Packs per outer box	25
EAN/UPC - Case	8718696673119


T12 Standard

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
F40T12/D-765 25 PK	40.5 mm	1,199.4 mm	1,206.5 mm	1,204.1 mm	1,213.6 mm

Photometric data



Spectral Power Distribution Colour - F40T12/D-765 25 PK

