

Flexo Print

TL 140W/03

Tubular low-pressure mercury vapour discharge lamps

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life to 50% Failures (Nom)	3,000 h

Light Technical	
Color Code	03
Color Designation	Super Actinic
Chromaticity Coordinate X (Nom)	175
Chromaticity Coordinate Y (Nom)	45
UV Depreciation at 1000 h	30 %
UV Depreciation at 2000 h	40 %
UV Depreciation at 500 h	20 %

Operating and Electrical	
Power Consumption	140 W
Lamp Current (Nom)	1.46 A
Voltage (Nom)	118 V
Voltage (Nom)	118 V

Mechanical and Housing	
Bulb Shape	T38 [T 38mm]


UV	
UV-A Radiation 100Hr (IEC)	1.00 W

Product Data	
Order product name	TL 140W/03
Full product name	TL 140W/03
Full product code	871150072094840
Order code	928012700303
Material Nr. (12NC)	928012700303
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500720948
Numerator - Packs per outer box	25
EAN/UPC - Case	8711500720955


Flexo Print

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL 140W/03	40.5 mm	1,500 mm	1,507.1 mm	1,504.7 mm	1,514.2 mm



Photometric data



Spectral Power Distribution Colour - TL 140W/03

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.