



# Actinic BL TL(-K)/TL-D(-K)

## Actinic BL TL-DK 30W/10

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers.

### Product data


General Information		Voltage (Nom)	
Cap base	G13 [ Medium Bi-Pin Fluorescent]		45 V
Main application	Insect traps	Approval and Application	
Life to 50% failures (nom.)	2000 h	Mercury (Hg) content (nom.)	8.0 mg
Useful life (nom.)	2000 h	UV	
Light Technical		UV-B/UV-A (IEC)	02 %
Colour code	10	UV-A radiation 100 hours (IEC)	6.6 W
Colour designation	Actinic	Product Data	
Chromaticity coordinate X (nom.)	225	Full product code	871150089346840
Chromaticity coordinate Y (nom.)	230	Order product name	ACTINIC BL TL-DK - 30W/10 1SL
Depreciation at 500 Hours	15 %	EAN/UPC – product	8711500893468
Depreciation at 1000 Hours	25 %	Order code	89346840
Depreciation at 500 Hours	40 %	Numerator – quantity per pack	1
Operating and Electrical		Numerator – packs per outer box	25
Power (Rated) (Nom)	30 W	Material no. (12NC)	928019501029
Lamp current (nom.)	0.805 A	Net weight (piece)	59.600 g

# Actinic BL TL(-K)/TL-D(-K)

## Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

## Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
ACTINIC BL TL-DK - 30W/10 1SL	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm

TL-DK 30W/10

## Photometric data

