



# TL-D Standard Colours

## TL-D 15W/54-765 SLV/25

TL-D Standard Colors lamps (tube diameter of 26 mm) create atmospheres from warm white to cool daylight. Lamps with moderate efficacy and color rendering.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Controls and Dimming	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Dimmable	Yes
Life to 50% Failures (Nom)	13,000 hour(s)		
Light Technical		Mechanical and Housing	
Color Code	54-765	Bulb Shape	T8 [26 mm (T8)]
Luminous Flux	725 lumen		
Color Designation	Cool Daylight	Approval and Application	
Correlated Color Temperature (Nom)	6200 K	Mercury (Hg) Content (Nom)	8.0 mg
Color rendering index (CRI)	72	Energy Consumption kWh/1000 h	20 kWh
Operating and Electrical		Product Data	
Power Consumption	15.0 W	Full product code	871150072221840
Lamp Current (Nom)	0.310 A	Order product name	TL-D 15W/54-765 SLV/25
Voltage (Nom)	51 V	Order code	928024805461
Voltage (Nom)	51 V	Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	25
		Material Nr. (12NC)	928024805461
		Full product name	TL-D 15W/54-765 SLV/25


# TL-D Standard Colours

EAN/UPC - Case	8711500722225
EAN/UPC - Product/Case	8711500722218

## Dimensional drawing


Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 15W/54-765 SLV/25	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm

## Photometric data




Spectral Power Distribution Colour - TL-D 15W/54-765 SLV/25

## Lifetime



Life Expectancy Diagram - TL-D 15W/54-765 SLV/25



Life Expectancy Diagram - TL-D 15W/54-765 SLV/25

## TL-D Standard Colours

### Lifetime

Lumen Maintenance Diagram - TL-D 15W/54-765 SLV/25

