



MASTER TL-D Food

MASTER TL-D Food 30W/79 1SL/25

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Product data

General Information	
Cap base	G13 [Medium Bi-Pin Fluorescent]
Life to 50% failures (nom.)	15000 h
Life to 50% failures preheat (nom.)	20000 h

Light Technical	
Colour Code	79
Lamp Luminous Flux 25°C EL (Nom)	1300 lm
Colour Designation	Food
Lumen maintenance 2,000 hours (nom.)	90 %
Lumen maintenance 5,000 hours (nom.)	85 %
Colour Temperature, horizontal (Nom)	3800 K
Lamp Luminous Efficacy EM (Nom)	43 lm/W
Colour Rendering Index,horiz (Nom)	74

Operating and Electrical	
Power (Rated) (Nom)	30.0 W
Lamp current (nom.)	0.360 A
Voltage (Nom)	98 V

Controls and Dimming	
Dimmable	yes

Approval and Application	
Energy efficiency label (EEL)	B
Mercury (Hg) content (nom.)	5.0 mg
Energy Consumption kWh/1000 h	37 kWh


Product Data	
Full product code	871150070624940
Order product name	MASTER TL-D Food 30W/79 SLV/25
EAN/UPC – product	8711500706249
Order code	70624940
Local Code	9280-254-02006
Numerator – quantity per pack	1
Numerator – packs per outer box	25
Material no. (12NC)	928025402043
Net weight (piece)	113.000 g
ILCOS Code	FD-30/38/2A-E-G13

MASTER TL-D Food

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Food 30W/79 SLV/25	28 mm	894.6 mm	901.7 mm	899.3 mm	908.8 mm

TL-D Food 30W/79



Photometric data



Lightcolour /79

Lightcolour /79

Lifetime



MASTER TL-D Food

Lifetime

