



# TL-D Standard Colours

## TL-D 18W/29-530 1SL/25

TL-D Standard Colors lamps (tube diameter of 26 mm) create atmospheres from warm white to cool daylight. Lamps with moderate efficacy and color rendering.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life to 50% Failures (Nom)	13,000 hour(s)
Light Technical	
Color Code	29-530
Luminous Flux	1,250 lumen
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2900 K
Color rendering index (CRI)	51
Operating and Electrical	
Power Consumption	18.0 W
Lamp Current (Nom)	0.360 A
Voltage (Nom)	59 V
Voltage (Nom)	59 V


Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	T8 [26 mm (T8)]
Approval and Application	
Mercury (Hg) Content (Nom)	8.0 mg
Product Data	
Full product code	872790085834100
Order product name	TL-D 18W/29-530 1SL/25
Order code	928048002953
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	928048002953
Full product name	TL-D 18W/29-530 1SL/25
EAN/UPC - Case	6923410798463



TL-D Standard Colours


EAN/UPC - Product/Case	6923410798098
------------------------	---------------

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 18W/29-530 1SL/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

Photometric data




Spectral Power Distribution Colour - TL-D 18W/29-530 1SL/25

Lifetime



Life Expectancy Diagram - TL-D 18W/29-530 1SL/25




Life Expectancy Diagram - TL-D 18W/29-530 1SL/25



TL-D Standard Colours

Lifetime



Lumen Maintenance Diagram - TL-D 18W/29-530 1SL/25

