



# TL-D Standard Colours

## TL-D 36W/29-530 1SL/25

TL-D Standard Colors lamps (tube diameter of 26 mm) create atmospheres from warm white to cool daylight. Lamps with moderate efficacy and color rendering.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data


General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life to 50% Failures (Nom)	13,000 hour(s)
Light Technical	
Color Code	29-530
Luminous Flux	2,975 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2900 K
Color rendering index (CRI)	51
Operating and Electrical	
Power Consumption	36.0 W
Lamp Current (Nom)	0.440 A
Voltage (Nom)	103 V
Voltage (Nom)	103 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	T8
Approval and Application	
Mercury (Hg) Content (Nom)	8.0 mg
Product Data	
Order product name	TL-D 36W/29-530 1SL/25
Full product name	TL-D 36W/29-530 1SL/25
Full product code	694793919442100
Order code	928048502953
Material Nr. (12NC)	928048502953
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6947939194421
Numerator - Packs per outer box	25

TL-D Standard Colours


EAN/UPC - Case	6922341996337
----------------	---------------

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 36W/29-530 1SL/25	28 mm	1,199.4 mm	1,206.5 mm	1,204.1 mm	1,213.6 mm

Photometric data




Spectral Power Distribution Colour - TL-D 36W/29-530 1SL/25

Lifetime




Life Expectancy Diagram - TL-D 36W/29-530 1SL/25



Life Expectancy Diagram - TL-D 36W/29-530 1SL/25

TL-D Standard Colours

Lifetime



Lumen Maintenance Diagram - TL-D 36W/29-530 1SL/25

