



# MSR Hot Restrike

## MSR 400 HR 1CT/4

Thanks to an optimized color temperature and a high color rendering index, the MSR Hot Restrike creates perfect 'daylight' in any condition. Also, the single ended lamp design enables hot re-ignition, which ensures daylight lighting and superb color rendition is always instantly available. They also incorporate the innovative P3 technology, developed by Philips, which allows use at higher temperatures and therefore extends lifetime and consistency of high-quality light output.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: [www.lamprecycle.org](http://www.lamprecycle.org) or 1-800-555-0050

### Product data


General Information		Color rendering index (CRI)	
Cap-Base	GZZ9.5		92
Operating Position	UNIVERSAL [Any or Universal (U)]	Arc Length O (Nom)	6.0 mm
Life to 50% Failures (Nom)	1,000 hour(s)	<b>Operating and Electrical</b>	
<b>Light Technical</b>		Power Consumption	400 W
Color Code	- [Not Specified]	Lamp Current (Nom)	7 A
Luminous Flux (Min)	28,080 lm	<b>Controls and Dimming</b>	
Luminous Flux	31,200 lm	Dimmable	Yes
Chromaticity Coordinate X (Nom)	326	<b>Product Data</b>	
Chromaticity Coordinate Y (Nom)	321	Order product name	MSR 400 HR 1CT/4
Correlated Color Temperature (Nom)	5830 K	Full product name	MSR 400 HR 1CT/4
Luminous Efficacy (rated) (Nom)	78 lm/W		

# MSR Hot Restrike

Full product code	871829122796000
Order code	287268
Material Nr. (12NC)	928050205115
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291227960


Numerator - Packs per outer box	4
EAN/UPC - Case	8718291227977

## Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F (min)	F
MSR 400	15/16	1/4	2-3/8	2-7/16	2-3/8	4-3/8	1 inch	15/16	15/16
HR 1CT/4	inch	inch	inch	inch	inch	inch		inch	inch

## Photometric data



Spectral Power Distribution Colour - MSR 400 HR 1CT/4

