

HPL-N

HPL-N 125W/542 E27 1CT/24

Standard High Pressure Mercury lamp

Warnings and Safety

- For use with control gear designed for high-pressure mercury lamps
- For use with control gear designed for high-pressure mercury lamps
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	E27 [E27]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	20,000 hour(s)

Light Technical	
Color Code	542 [CCT of 4200K]
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	374
Chromaticity Coordinate Y (Nom)	373
Correlated Color Temperature (Nom)	4100 K
Luminous Efficacy (rated) (Nom)	50 lm/W
Color rendering index (CRI)	46

Operating and Electrical	
Power Consumption	125.0 W
Voltage (Nom)	125 V
Voltage (Nom)	125 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Coated glass
Bulb Material	Soft Glass
Bulb Shape	E75 [E 75mm]


Approval and Application	
Mercury (Hg) Content (Nom)	19.0 mg
Energy Consumption kWh/1000 h	137 kWh

HPL-N

Product Data	
Order product name	HPL-N 125W/542 E27 1CT/24
Full product name	HPL-N 125W/542 E27 1CT/24
Full product code	692059027779500
Order code	928052007391
Material Nr. (12NC)	928052007391


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6920590277795
Numerator - Packs per outer box	24
EAN/UPC - Case	6920590277801

Dimensional drawing




Product	D (max)	C (max)
HPL-N 125W/542 E27 1CT/24	76 mm	173 mm

Photometric data




Spectral Power Distribution Colour - HPL-N 125W/542 E27 1CT/24

Lifetime



Life Expectancy Diagram - HPL-N 125W/542 E27 1CT/24



Lumen Maintenance Diagram - HPL-N 125W/542 E27 1CT/24



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.