



# MASTERColour CDM-R

# MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT

Range of compact, high-efficiency, discharge reflector lamps with a stable colour over lifetime and a crisp, sparkling light

#### **Warnings and Safety**

- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. Color 830 lamps may also use electromagnetic gear.
- · Use only with electronic control gear. Colour 830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information	
Cap-Base	E27 [E27]
Operating Position	UNIVERSAL [Any or Universal (U)]
Switching Cycle	1,000
Life to 50% Failures (Nom)	8,000 hour(s)
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	30 degree(s)
Luminous Intensity (Nom)	7,400 cd
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.431
Chromaticity Coordinate Y (Nom)	0.400
Correlated Color Temperature (Nom)	3000 K

Color rendering index (CRI)	81	
LLMF At End Of Nominal Lifetime (Nom) 48 %		
Luminous Flux in 90° Cone (Rated)	2,000 lm	
Operating and Electrical		
Power Consumption	39.1 W	
Warm-up time to 60% light	120 s	
Voltage (Nom)	86 V	
Voltage (Nom)	86 V	
Controls and Dimming		
Dimmable	No	


Datasheet, 2023, April 15 data subject to change

# **MASTERColour CDM-R**

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	PAR30L [PAR 3.75 inch/95mm Long]
Approval and Application	
Mercury (Hg) Content (Nom)	2.8 mg
Energy Consumption kWh/1000 h	42 kWh
Product Data	
Order product name	MASTERC CDM-R 35W/830 E27 PAR30L 30D
	1CT

Full product name	MASTERC CDM-R 35W/830 E27 PAR30L 30D
	1CT
Full product code	871150021170500
Order code	928071000691
Material Nr. (12NC)	928071000691
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500211705
Numerator - Packs per outer box	6
EAN/UPC - Case	8711500211712


## Dimensional drawing




 Product
 D (max)
 D (max)
 C (max)
 C

 MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT
 97 mm
 95 mm
 123 mm
 120 mm

### Photometric data






Light Distribution Diagram - MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT

Spectral Power Distribution Colour - MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT

## **MASTERColour CDM-R**

## Lifetime





Life Expectancy Diagram - MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT

Lumen Maintenance Diagram - MASTERC CDM-R 35W/830 E27 PAR30L 30D 1CT



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.