



MSR

MSR 1200 1CT/3

MSR – bright vivid colours, always The high colour rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colours of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set–up and convenience.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	G22			
Operating Position	UNIVERSAL [Any or Universal (U)]			
Life to 50% Failures (Nom)	800 h			
Light Technical				
Color Code	- [Not Specified]			
Luminous Flux	103,000 lm			
Chromaticity Coordinate X (Nom)	325			
Chromaticity Coordinate Y (Nom)	327			
Correlated Color Temperature (Nom)	5900 K			
Luminous Efficacy (rated) (Nom)	88 lm/W			
Color rendering index (CRI)	80			

Arc Length O (Nom)	10.0 mm				
Operating and Electrical					
Power Consumption	1,200 W				
Lamp Current (Nom)	13.8 A				
Controls and Dimming					
Dimmable	No				
Product Data					
Order product name	MSR 1200 1CT/3				
Full product name	MSR 1200 1CT/3				
Full product code	872790091121300				
Local code description	MSR1200W				


Datasheet, 2023, April 16 data subject to change

MSR

Order code	928078105114
Material Nr. (12NC)	928078105114
Local order code	MSR1200W
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900911213


Numerator - Packs per outer box	3
EAN/UPC - Case	8727900911220

Dimensional drawing



Product	D (max)	0	L (min)	L (max)	L	C (max)	F
MSR 1200 1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm

Photometric data



Spectral Power Distribution Colour - MSR 1200 1CT/3



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.