



# MASTER CityWhite CDO-TT



# MASTER CityWhite CDO-TT Plus 150W/828 E40

Ceramic metal halide lamp with clear tubular outer bulb shape, used in outdoor offering pleasant white light

### **Warnings and Safety**

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- $\boldsymbol{\cdot}$  The luminaire must be able to contain hot lamp parts if the lamp ruptures
- $\cdot$  Lamps may use electronic or electromagnetic control gear
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)

### **Product data**

General Information				
Cap base	E40			
Operating position	UNIVERSAL [Any or Universal (U)]			
Flux measurement reference	Sphere			
Life to 50% failures (nom.)	27,000 h			
Light Technical				
Colour Code	828 [CCT of 2800K]			
Luminous Flux	16,400 lm			
Colour designation	Warm White (WW)			
Chromaticity Coordinate X (Nom)	0.447			
Chromaticity Coordinate Y (Nom)	0.4			
Correlated Colour Temperature	2800 K			
Luminous efficacy (rated) (nom.)	110 lm/W			
Colour rendering index (CRI)	87			
Arc Length O (Nom)	10 mm			

Operating and Electrical	
Power Consumption	148.5 W
Voltage (nom.)	99 V
Voltage (nom.)	99 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Lamp Finish	Clear
Bulb shape	T46
Approval and Application	
Energy Efficiency Class	F
Mercury (Hg) content (max.)	15.8 mg
Mercury (Hg) content (nom.)	15.8 mg
Energy consumption kWh/1,000 hours	149 kWh


Datasheet, 2023, April 16 data subject to change

# **MASTER CityWhite CDO-TT**

EPREL registration number	473327
Product Data	
Order product name	MASTER CityWh CDO-TT Plus 150W/828 E40
Full product name	MASTER CityWhite CDO-TT Plus 150W/828 E40
Full EOC	871829112034600
Order code	12034600


Material no. (12 NC)	928082219231
SAP numerator – quantity per pack	1
EAN/UPC — Product/Case	8718291120346
Numerator – packs per outer box	12
EAN/UPC - Case	8718291120353

# Dimensional drawing




Product	D (max)	0	L	C (max)
MASTER CityWh CDO-TT Plus 150W/828 E40	47 mm	10 mm	132 mm	211 mm

# Photometric data




Light Distribution Diagram - MASTER CityWh CDO-TT Plus 150W/828 E40




Spectral Power Distribution Colour - MASTER CityWh CDO-TT Plus 150W/828 E40

# **MASTER CityWhite CDO-TT**

### Lifetime





Life Expectancy Diagram - MASTER CityWh CDO-TT Plus 150W/828 E40

Lumen Maintenance Diagram - MASTER CityWh CDO-TT Plus 150W/828 E40

