



MASTERColour CDM-T

MASTERC CDM-T 70W/830 G12 1CT/12

Range of single-ended, compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light

Warnings and Safety

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- $\boldsymbol{\cdot}$ The luminaire must be able to contain hot lamp parts if the lamp ruptures
- \cdot Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	G12			
Operating Position	UNIVERSAL [Any or Universal (U)]			
Flux measurement reference	Sphere			
Life to 50% Failures (Nom)	12,000 hour(s)			
Light Technical				
Color Code	830 [CCT of 3000K]			
Luminous Flux	6,200 lm			
Color Designation	Warm White (WW)			
Chromaticity Coordinate X (Nom)	0.434			
Chromaticity Coordinate Y (Nom)	0.398			
Correlated Color Temperature (Nom)	3000 K			

Luminous Efficacy (rated) (Nom)	85 lm/W
Color rendering index (CRI)	84
Arc Length O (Nom)	7 mm
Operating and Electrical	
Power Consumption	73.2 W
Voltage (Nom)	88 V
Voltage (Nom)	88 V
Controls and Dimming	
Dimmable	No


Datasheet, 2023, April 16 data subject to change

MASTERColour CDM-T

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T19
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	4.6 mg
Mercury (Hg) Content (Nom)	4.6 mg
Energy Consumption kWh/1000 h	74 kWh
EPREL Registration Number	473328
Product Data	
Order product name	MASTERC CDM-T 70W/830 G12 1CT/12


Full product name	MASTERC CDM-T 70W/830 G12 1CT/12				
Full product code	871150019699615				
Order code	928082305125				
Material Nr. (12NC)	928082305125				
Numerator - Quantity Per Pack	1				
EAN/UPC - Product/Case	8711500196996				
Numerator - Packs per outer box	12				
EAN/UPC - Case	8711500197009				


Dimensional drawing




Product	D (max)	D	0	L (min)	L (max)	L	C (max)
MASTERC CDM-T	20 mm	0.75 inch	7 mm	55 mm	57 mm	56 mm	103 mm
70W/830 G12 1CT/12							

Photometric data









Light Distribution Diagram - MASTERC CDM-T 70W/830 G12 1CT/12

Spectral Power Distribution Colour - MASTERC CDM-T 70W/830 G12 1CT/12

MASTERColour CDM-T

Lifetime





Life Expectancy Diagram - MASTERC CDM-T 70W/830 G12 1CT/12

Lumen Maintenance Diagram - MASTERC CDM-T 70W/830 G12 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.