



MASTERColour CDM-T 陶瓷複金屬燈

MASTERC CDM-T 70W/830 G12 1CT/12

精巧、高效率單端型放電式反射燈具系列，光色歷久如新，光線清晰明亮

安全提示

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般資訊	
燈座基底	G12
操作位置	UNIVERSAL [任何或通用 (U)]
壽命 (故障率 50%) (標稱)	12,000 h
照明技術	
色碼	830 [CCT of 3000K]
色彩名稱	暖白光 (WW)
色度坐標 X (標稱)	0.432
色度坐標 Y (Nom)	0.395
相關色彩溫度 (規範)	3000 K
光效 (額定) (標準)	85 lm/W
演色性指數 (CRI)	84


電弧長 Ø (標稱)	7 mm
運轉與電力	
耗電量	73.2 W
電壓 (標稱)	88 V
電壓 (標稱)	88 V
控制與調光	
可調光	否
機械與外罩	
燈泡表層	透明
燈泡形狀	T19

MASTERCoulour CDM-T 陶瓷複金屬燈

認證與應用	
汞 (Hg) 含量 (標稱)	4.6 mg
能源消耗 kWh/1000 h	80 kWh
產品資料	
下訂產品名稱	MASTERC CDM-T 70W/830 G12 1CT/12
完整產品名稱	MASTERC CDM-T 70W/830 G12 1CT/12
完整產品代碼	871869648447000


訂單代碼	928082305129
材質 Nr. (12NC)	928082305129
分子 - 每個包裝的數量	1
EAN/UPC - 產品/案例	8718696484470
分子 - 每一外盒包裝	12
EAN/UPC - 箱	8718696484487

二维绘图




Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERC CDM-T 70W/830 G12 1CT/12	20 mm	0.75 in	7 mm	55 mm	57 mm	56 mm	103 mm

光度数据




Light Distribution Diagram - MASTERC CDM-T 70W/830 G12 1CT/12




Spectral Power Distribution Colour - MASTERC CDM-T 70W/830 G12 1CT/12

MASTERColour CDM-T 陶瓷複金屬燈

壽命



Life Expectancy Diagram - MASTERC CDM-T 70W/830 G12 1CT/12



Lumen Maintenance Diagram - MASTERC CDM-T 70W/830 G12 1CT/12

