



MASTERColour CDM-T

MASTERC CDM-T 150W/830 G12 1CT

Range of single-ended, compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Luminous Efficacy (rated) (Nom)	
Cap-Base	G12 [G12]	88 lm/W	
Operating Position	UNIVERSAL [Any or Universal (U)]	Color rendering index (CRI)	
Flux measurement reference	Sphere	88	
Life to 50% Failures (Nom)	12,000 hour(s)	Arc Length O (Nom)	
		9 mm	
Light Technical		Operating and Electrical	
Color Code	830 [CCT of 3000K]	Power Consumption	
Luminous Flux	13,000 lm	150.1 W	
Color Designation	Warm White (WW)	Voltage (Nom)	
Chromaticity Coordinate X (Nom)	0.434	96 V	
Chromaticity Coordinate Y (Nom)	0.398	Voltage (Nom)	
Correlated Color Temperature (Nom)	3000 K	Controls and Dimming	
		Dimmable	
		No	

MASTERCoulour CDM-T


Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T19 [T 19mm]

Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	14.3 mg
Mercury (Hg) Content (Nom)	14.3 mg
Energy Consumption kWh/1000 h	151 kWh
EPREL Registration Number	473335

Product Data	
Order product name	MASTERC CDM-T 150W/830 G12 1CT


Full product name	MASTERC CDM-T 150W/830 G12 1CT
Full product code	871150019780115
Order code	928083705125
Material Nr. (12NC)	928083705125
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500197801
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500197818

Dimensional drawing




Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERC CDM-T 150W/830 G12 1CT	20 mm	0.75 inch	9 mm	55 mm	57 mm	56 mm	110 mm

Photometric data





Light Distribution Diagram - MASTERC CDM-T 150W/830 G12 1CT



Spectral Power Distribution Colour - MASTERC CDM-T 150W/830 G12 1CT

MASTERColour CDM-T

Lifetime



Life Expectancy Diagram - MASTERC CDM-T 150W/830 G12 1CT

Lumen Maintenance Diagram - MASTERC CDM-T 150W/830 G12 1CT

