



MASTERColour CDM-TC

MASTERColour CDM-TC 35W/830 G8.5 1CT/12

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Arc Length O (Nom)	
Cap-Base	G8.5	5 mm	
Operating Position	UNIVERSAL [Any or Universal (U)]		
Life to 50% Failures (Nom)	12,000 hour(s)		
Light Technical		Operating and Electrical	
Color Code	830 [CCT of 3000K]	Power Consumption	39.1 W
Color Designation	Warm White (WW)	Voltage (Nom)	88 V
Chromaticity Coordinate X (Nom)	0.432	Voltage (Nom)	88 V
Chromaticity Coordinate Y (Nom)	0.394		
Correlated Color Temperature (Nom)	3000 K	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	79 lm/W	Dimmable	No
Color rendering index (CRI)	81		
		Mechanical and Housing	
		Bulb Finish	Clear
		Bulb Material	UV-Block Quartz

MASTERColour CDM-TC

Bulb Shape	T14
Approval and Application	
Mercury (Hg) Content (Nom)	3.1 mg
Energy Consumption kWh/1000 h	43 kWh
Product Data	
Order product name	MASTERC CDM-TC 35W/830 G8.5 1CT/12
Full product name	MASTERColour CDM-TC 35W/830 G8.5 1CT/12


Full product code	871869648459300
Order code	48459300
Material Nr. (12NC)	928085205129
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696484593
Numerator - Packs per outer box	12
EAN/UPC - Case	8718696484609

Dimensional drawing




Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERC CDM-TC 35W/830 G8.5 1CT/12	15 mm	0.5 inch	5 mm	51 mm	53 mm	52 mm	85 mm

Photometric data




Light Distribution Diagram - MASTERC CDM-TC 35W/830 G8.5 1CT/12




Spectral Power Distribution Colour - MASTERC CDM-TC 35W/830 G8.5 1CT/12

MASTERC colour CDM-TC

Lifetime



Lumen Maintenance Diagram - MASTERC CDM-TC 35W/830 G8.5 1CT/12



Life Expectancy Diagram - MASTERC CDM-TC 35W/830 G8.5 1CT/12

