

MASTERColour CDM-TC 陶瓷複金屬燈

MASTERC CDM-TC 70W/830 G8.5 1CT/12

超精巧、高效率單端型放電燈，光色歷久如新，光線清晰明亮

安全提示

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般資訊	
燈座基底	G8.5
操作位置	UNIVERSAL [任何或通用 (U)]
壽命 (故障率 50%) (標稱)	12,000 h

照明技術	
色碼	830 [CCT of 3000K]
色彩名稱	暖白光 (WW)
色度坐標 X (標稱)	0.439
色度坐標 Y (Nom)	0.398
相關色彩溫度 (規範)	3000 K
光效 (額定) (標準)	86 lm/W
演色性指數 (CRI)	83
電弧長 O (標稱)	7 mm

運轉與電力	
耗電量	73.2 W
電壓 (標稱)	83 V
電壓 (標稱)	83 V

控制與調光	
可調光	否

機械與外罩	
燈泡表層	透明
燈泡材質	抗 UV 石英
燈泡形狀	T14

認證與應用	
汞 (Hg) 含量 (標稱)	4.6 mg

MASTERColour CDM-TC 陶瓷複金屬燈


能源消耗 kWh/1000 h	80 kWh

材質 Nr. (12NC)	928086505129
分子 - 每個包裝的數量	1
EAN/UPC - 產品/案例	8718696484630
分子 - 每一外盒包裝	12
EAN/UPC - 箱	8718696484647

產品資料


下訂產品名稱	MASTERC CDM-TC 70W/830 G8.5 1CT/12
完整產品名稱	MASTERC CDM-TC 70W/830 G8.5 1CT/12
完整產品代碼	871869648463000
訂單代碼	928086505129


二维绘图




Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERC CDM-TC 70W/830 G8.5 1CT/12	15 mm	0.5 in	7 mm	51 mm	53 mm	52 mm	85 mm

光度数据






Light Distribution Diagram - MASTERC CDM-TC 70W/830 G8.5 1CT/12




Spectral Power Distribution Colour - MASTERC CDM-TC 70W/830 G8.5 1CT/12

MASTERColour CDM-TC 陶瓷複金屬燈

壽命



Lumen Maintenance Diagram - MASTERC CDM-TC 70W/830 G8.5 1CT/12



Life Expectancy Diagram - MASTERC CDM-TC 70W/830 G8.5 1CT/12

© 2023 Signify Holding 保留一切權利。 Signify 不對本協議所含括資訊之準確性及完整性提供任何聲明或保證，對以此訊息為依據採取的任何行動亦概不負責。 除非 Signify 同意，本文件提及之資訊並非任何商業合約，亦不構成任何報價或合約任一部分。 Philips 與 Philips Shield Emblem 均屬 Koninklijke Philips N.V 註冊商標。