PHILIPS Lighting



MASTERColour CDM-TC

MASTERColour CDM-TC 70W/830 G8.5 1CT/12

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- \cdot Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

neral Information		Color rendering index (CRI)	83
Cap-Base	G8.5	Arc Length O (Nom)	7 mm
Operating Position	UNIVERSAL [Any or Universal (U)]		
Flux measurement reference	Sphere	Operating and Electrical	
Life to 50% Failures (Nom)	12,000 hour(s)	Power Consumption	73.2 W
		Voltage (Nom)	83 V
Light Technical		Voltage (Nom)	83 V
Color Code	830 [CCT of 3000K]		
uminous Flux	6,300 lm	Controls and Dimming	
Color Designation	Warm White (WW)	Dimmable	No
Chromaticity Coordinate X (Nom)	0.434		
Chromaticity Coordinate Y (Nom)	0.398	Mechanical and Housing	
Correlated Color Temperature (Nom)	3000 K	Bulb Finish	Clear
Luminous Efficacy (rated) (Nom)	86 lm/W	Bulb Material	UV-Block Quartz

MASTERColour CDM-TC


Bulb Shape	T14
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	4.6 mg
Mercury (Hg) Content (Nom)	4.6 mg
Energy Consumption kWh/1000 h	74 kWh
EPREL Registration Number	473344
Product Data	

Full product name	MASTERColour CDM-TC 70W/830 G8.5 1CT/12			
Full product code	871150020167615			
Order code	20167615			
Material Nr. (12NC)	928086505131			
Numerator - Quantity Per Pack	1			
EAN/UPC - Product/Case	8711500201676			
Numerator - Packs per outer box	12			
EAN/UPC - Case	8711500201683			


Product Data


Order product name	MASTERC CDM-TC 70W/830 G8.5 1CT/12
--------------------	------------------------------------

Dimensional drawing



Photometric data






180°

150°

210°

Light Distribution Diagram - MASTERC CDM-TC 70W/830 G8.5 1CT/12

Product	D (max)	D	0	L (min)	L (max)	L	C (max)
MASTERC CDM-TC	15 mm	0.5 inch	7 mm	51 mm	53 mm	52 mm	85 mm
70W/830 G8.5 1CT/12							




Spectral Power Distribution Colour - MASTERC CDM-TC 70W/830 G8.5 1CT/12

MASTERColour CDM-TC

Lumen Maintenance Diagram - MASTERC CDM-TC 70W/830 G8.5 1CT/12

Lifetime



Life Expectancy Diagram - MASTERC CDM-TC 70W/830 G8.5 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 15 - data subject to change