



# CDM-SA/T

## CDM-SA/T 150W/942 1CT/12

With a high luminous efficacy producing more lumens per watt than standard Architainment lamps, the CDM-SA/T is the greener alternative to light up the night. In addition, the optimal lamp filling and short arc of the lamp create a high beam intensity and excellent color rendering.

### Product data

General Information	
Cap base	G12 [ G12]
Operating position	UNIVERSAL [ Any or Universal (U)]
Main application	Dynamic Architectural
Life to 50% failures (nom.)	9000 h
Light Technical	
Colour code	942 [ CCT of 4,200 K]
Luminous flux (min.)	12000 lm
Luminous flux (nom.)	13330 lm
Colour designation	Cool White (CW)
Chromaticity coordinate X (nom.)	380
Chromaticity coordinate Y (nom.)	360
Correlated colour temperature (nom.)	4200 K
Luminous efficacy (rated) (nom.)	86 lm/W
Color rendering index (nom.)	95
Operating and Electrical	
Power (Rated) (Nom)	150 W
Lamp current (nom.)	1.8 A
Ignition supply voltage (min.)	198 V


Controls and Dimming	
Dimmable	No
Approval and Application	
Mercury (Hg) content (max.)	11.9 mg
Luminaire Design Requirements	
Bulb temperature (max.)	650 °C
Pinch temperature (max.)	350 °C
Product Data	
Full product code	871150020094515
Order product name	CDM-SA/T 150W/942 1CT/12
EAN/UPC – product	8711500200945
Order code	20094515
Numerator – quantity per pack	1
Numerator – packs per outer box	12
Material no. (12NC)	928086605103
Net weight (piece)	0.030 kg

# CDM-SA/T

## Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

## Dimensional drawing



CDM-SA/T 150W/942

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
CDM-SA/T	20 mm	6	55 mm	57 mm	56	110 mm	31 mm	30	29 mm
150W/942		mm			mm			mm	
1CT/12									

## Photometric data

