



# MASTERColour CDM-TP

# MASTERC CDM-TP 70W/830 PG12-2 1CT/12

Range of protected, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light to be used in open luminairs

### **Warnings and Safety**

- · Lamps may use electronic or electromagnetic control gear
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information				
Cap-Base	PG12-2			
Operating Position	UNIVERSAL [Any or Universal (U)]			
Life to 50% Failures (Nom)	16,000 hour(s)			
Light Technical				
Color Code	830 [CCT of 3000K]			
Color Designation	Warm White (WW)			
Chromaticity Coordinate X (Nom)	428			
Chromaticity Coordinate Y (Nom)	401			
Correlated Color Temperature (Nom)	3000 K			
Luminous Efficacy (rated) (Nom)	82 lm/W			
Color rendering index (CRI)	80			
Arc Length O (Nom)	7 mm			
·	<u> </u>			

Operating and Electrical	
Power Consumption	73.2 W
Voltage (Nom)	90 V
Voltage (Nom)	90 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T31
Approval and Application	-
Energy Efficiency Class	G
Mercury (Hg) Content (Nom)	5.2 mg


Datasheet, 2024, March 21 data subject to change

# **MASTERColour CDM-TP**

Energy Consumption kWh/1000 h	81 kWh
Product Data	
Order product name	MASTERC CDM-TP 70W/830 PG12-2 1CT/12
Full product name	MASTERC CDM-TP 70W/830 PG12-2 1CT/12
Full product code	871150020127015
Order code	928086909230


Material Nr. (12NC)	928086909230
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500201270
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500201287

# Dimensional drawing




Product	D (max)	0	L (min)	L (max)	L	C (max)
MASTERC CDM-TP 70W/830	32.00 mm	7 mm	89 mm	93 mm	91 mm	149 mm
PG12-21CT/12						


## Photometric data



Spectral Power Distribution Colour - MASTERC CDM-TP 70W/830 PG12-2 1CT/12

## Lifetime





Life Expectancy Diagram - MASTERC CDM-TP 70W/830 PG12-2 1CT/12

Lumen Maintenance Diagram - MASTERC CDM-TP 70W/830 PG12-2 1CT/12

# **MASTERColour CDM-TP**



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.