



MASTERColour CDM-TP

MASTERC CDM-TP 150W/830 PGX12-2 1CT/12

Range of protected, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light to be used in open luminaires

Warnings and Safety

- Lamps may use electronic or electromagnetic control gear
- Lamps may use electronic or electromagnetic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Luminous Efficacy (rated) (Nom)	88 lm/W
Cap-Base	PGX12-2 [PGX12-2]	Color rendering index (CRI)	86
Operating Position	UNIVERSAL [Any or Universal (U)]	Arc Length O (Nom)	9 mm
Life to 50% Failures (Nom)	16,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	150.1 W
Color Code	830 [CCT of 3000K]	Voltage (Nom)	98 V
Color Designation	Warm White (WW)	Voltage (Nom)	98 V
Chromaticity Coordinate X (Nom)	444		
Chromaticity Coordinate Y (Nom)	407		
Correlated Color Temperature (Nom)	3000 K		

MASTERC colour CDM-TP

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T31 [T 31mm]
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Nom)	15 mg
Energy Consumption kWh/1000 h	165 kWh


Product Data	
Order product name	MASTERC CDM-TP 150W/830 PGX12-2 1CT/12
Full product name	MASTERC CDM-TP 150W/830 PGX12-2 1CT/12
Full product code	871150020125615
Order code	928087009230
Material Nr. (12NC)	928087009230
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500201256
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500201263

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERC CDM-TP 150W/830 PGX12-2 1CT/12	32.00 mm	9 mm	89 mm	93 mm	91 mm	149 mm


Photometric data




Spectral Power Distribution Colour - MASTERC CDM-TP 150W/830 PGX12-2 1CT/12

MASTERC colour CDM-TP

Lifetime



Life Expectancy Diagram - MASTERC CDM-TP 150W/830 PGX12-2 1CT/12



Lumen Maintenance Diagram - MASTERC CDM-TP 150W/830 PGX12-2 1CT/12

