



# MASTER SON-T PIA Plus



## MST SON-T PIA Plus 250W E40 1SL/12

High Pressure Sodium lamp with clear tubular outer bulb, high output and long reliable lifetime

#### **Warnings and Safety**

- · Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### **Product data**

General Information					
Cap-Base	E40				
Operating Position	UNIVERSAL [Any or Universal (U)]				
Flux measurement reference	Sphere				
Life to 50% Failures (Nom)	36,000 hour(s)				
Light Technical					
Color Code	220 [CCT of 2000K]				
Luminous Flux	33,000 lm				
Chromaticity Coordinate X (Nom)	0.535				
Chromaticity Coordinate Y (Nom)	0.420				
Correlated Color Temperature (Nom)	2000 K				
Luminous Efficacy (rated) (Nom)	125 lm/W				
Color rendering index (CRI)	-				
Arc Length O (Nom)	64 mm				

Operating and Electrical	
Power Consumption	264 W
Voltage (Nom)	102 V
Voltage (Nom)	102 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T46
Approval and Application	
Energy Efficiency Class	E
Mercury (Hg) Content (Max)	15.1 mg
Mercury (Hg) Content (Nom)	15.1 mg
Energy Consumption kWh/1000 h	257 kWh


Datasheet, 2024, February 21 data subject to change

## **MASTER SON-T PIA Plus**

<b>EPREL Registration Number</b>	1436304
Product Data	
Order product name	MST SON-T PIA Plus 250W E40 1SL/12
Full product name	MST SON-T PIA Plus 250W E40 1SL/12
Full product code	871829118075300
Order code	928144709293


Material Nr. (12NC)	928144709293
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291180753
Numerator - Packs per outer box	12
EAN/UPC - Case	8718291180760


## Dimensional drawing




Product	D (max)	0	L	C (max)
MST SON-T PIA Plus 250W E40 1SL/12	48 mm	64 mm	158 mm	257 mm

#### Photometric data










Light Distribution Diagram - MST SON-T PIA Plus 250W E40 1SL/12

Spectral Power Distribution Colour - MST SON-T PIA Plus 250W E40 1SL/12

#### Lifetime







Lumen Maintenance Diagram - MST SON-T PIA Plus 250W E40 1SL/12

## **MASTER SON-T PIA Plus**



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.