

MASTER SOX-E

MASTER SOX-E 18W BY22d 1SL/12

Low Pressure Sodium lamp with improved efficacy

Warnings and Safety

- Lamps may use electronic or electromagnetic control gear

Product data

General Information	
Cap-Base	BY22D [BY22d]
Operating Position	H110 [Hanging +/-110D or Base Up (BU)]
Life to 50% Failures (Nom)	18,000 hour(s)

Light Technical	
Correlated Color Temperature (Nom)	1800 K
Luminous Efficacy (rated) (Nom)	100 lm/W

Operating and Electrical	
Power Consumption	18.0 W
Voltage (Nom)	57 V
Voltage (Nom)	57 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Shape	T50 [T 50mm]


Approval and Application	
Mercury (Hg) Content (Nom)	0 mg
Energy Consumption kWh/1000 h	21 kWh

Product Data	
Order product name	MASTER SOX-E 18W BY22d 1SL/12
Full product name	MASTER SOX-E 18W BY22d 1SL/12
Full product code	871150019280615
Order code	19280615
Material Nr. (12NC)	928145200008
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500192806
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500193407


MASTER SOX-E

Dimensional drawing

Product	D (max)	C (max)
MASTER SOX-E 18W BY22d 1SL/12	52 mm	216 mm




Photometric data




Light Distribution Diagram - MASTER SOX-E 18W BY22d 1SL/12

Lifetime



Life Expectancy Diagram - MASTER SOX-E 18W BY22d 1SL/12



Lumen Maintenance Diagram - MASTER SOX-E 18W BY22d 1SL/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com
2023, May 1 - data subject to change