



MASTER SOX-E

MASTER SOX-E 26W BY22D SLV/12

Low Pressure Sodium lamp with improved efficacy

Warnings and Safety

- Lamps may use electronic or electromagnetic control gear

Product data


General Information	
Cap base	BY22D [BY22d]
Operating position	H110 [Hanging +/-110D or Base Up (BU)]
Life to 50% failures (nom.)	18,000 h
Light Technical	
Correlated Colour Temperature	1800 K
Luminous efficacy (rated) (nom.)	140 lm/W
Operating and Electrical	
Power Consumption	27.0 W
Voltage (nom.)	69 V
Voltage (nom.)	69 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb shape	T50 [T 50 mm]

Approval and Application	
Mercury (Hg) content (nom.)	0 mg
Energy consumption kWh/1,000 hours	31 kWh
Product Data	
Order product name	MASTER SOX-E 26W BY22d 1SL/12
Full product name	MASTER SOX-E 26W BY22D SLV/12
Full EOC	871150017974615
Order code	17974615
Material no. (12 NC)	928145700008
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8711500179746
Numerator – packs per outer box	12
EAN/UPC – Case	8711500182692


MASTER SOX-E

Dimensional drawing

Product	D (max)	C (max)
MASTER SOX-E 26W BY22d 1SL/12	52 mm	311 mm




Photometric data




Light Distribution Diagram - MASTER SOX-E 26W BY22d 1SL/12

Lifetime



Life Expectancy Diagram - MASTER SOX-E 26W BY22d 1SL/12



Lumen Maintenance Diagram - MASTER SOX-E 26W BY22d 1SL/12

