



MASTER SOX-E

MASTER SOX-E 36W BY22D SLV/12

Low Pressure Sodium lamp with improved efficacy

Warnings and Safety

- Lamps may use electronic or electromagnetic control gear


Product data

General Information	
Cap-Base	BY22D [BY22d]
Operating Position	P20 [Parallel +/-20D or Horizontal(HOR)]
Life to 50% Failures (Nom)	18,000 hour(s)
Light Technical	
Correlated Color Temperature (Nom)	1800 K
Luminous Efficacy (rated) (Nom)	164 lm/W
Operating and Electrical	
Power Consumption	36.0 W
Voltage (Nom)	120 V
Voltage (Nom)	120 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	T50 [T 50mm]

Approval and Application	
Mercury (Hg) Content (Nom)	0 mg
Energy Consumption kWh/1000 h	40 kWh
Product Data	
Order product name	MASTER SOX-E 36W BY22d 1SL/12
Full product name	MASTER SOX-E 36W BY22D SLV/12
Full product code	871150017976015
Order code	17976015
Material Nr. (12NC)	928145800008
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500179760
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500182739



MASTER SOX-E

Dimensional drawing



Product	D (max)	C (max)
MASTER SOX-E 36W BY22d 1SL/12	52 mm	425 mm



Photometric data



Light Distribution Diagram - MASTER SOX-E 36W BY22d 1SL/12

Spectral Power Distribution Colour - MASTER SOX-E 36W BY22d 1SL/12

Lifetime



Life Expectancy Diagram - MASTER SOX-E 36W BY22d 1SL/12

Lumen Maintenance Diagram - MASTER SOX-E 36W BY22d 1SL/12

