



MASTER SDW-T



MASTER SDW-T 100W/825 PG12-1 1SL/12

Range of high-efficiency, discharge lamps with warm color to be used in open luminairs

Warnings and Safety

- · Use only with dedicated Philips control gear
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	PG12-1			
Operating Position	UNIVERSAL [Any or Universal (U)] Sphere			
Flux measurement reference				
Life to 50% Failures (Nom)	15,000 hour(s)			
Useful Life (Nom)	10,000 hour(s)			
Light Technical				
Color Code	825 [CCT of 2500K]			
Luminous Flux	5,100 lm			
Color Designation	Golden White			
Chromaticity Coordinate X (Nom)	0.478			
Chromaticity Coordinate Y (Nom)	0.415			
Correlated Color Temperature (Nom)	2500 K			
Luminous Efficacy (rated) (Nom)	52.58 lm/W			
Color rendering index (CRI)	83			
Arc Length O (Nom)	19 mm			

Operating and Electrical	
Power Consumption	97.0 W
Voltage (Nom)	97 V
Voltage (Nom)	97 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Hard Glass
Bulb Shape	T31
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	11.4 mg
Mercury (Hg) Content (Nom)	11.4 mg
Energy Consumption kWh/1000 h	97 kWh


Datasheet, 2024, March 21 data subject to change

MASTER SDW-T

EPREL Registration Number	473397
Product Data	
Order product name	MASTER SDW-T 100W/825 PG12-1 1SL/12
Full product name	MASTER SDW-T 100W/825 PG12-1 1SL/12
Full product code	871150073404415
Order code	928154109227


Material Nr. (12NC)	928154109227
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500734044
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500831163
'	

Dimensional drawing




Product	D (max)	0	L	C (max)
MASTER SDW-T 100W/825 PG12-1 1SL/12	32 mm	18.3 mm	91 mm	149 mm

Photometric data









Spectral Power Distribution Colour - MASTER SDW-T 100W/825 PG12-1 1SL/12

MASTER SDW-T

Lifetime





Life Expectancy Diagram - MASTER SDW-T 100W/825 PG12-1 1SL/12

Lumen Maintenance Diagram - MASTER SDW-T 100W/825 PG12-1 1SL/12



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.